

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** SPOT LIGHT

**Supplier's address:** -

**Model identifier:** 2220102

**Type of light source:**

|                                                     |      |                                 |     |
|-----------------------------------------------------|------|---------------------------------|-----|
| Lighting technology used:                           | LED  | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | GU10 |                                 |     |
| Mains or non-mains:                                 | MLS  | Connected light source (CLS):   | No  |
| Colour-tuneable light source:                       | No   | Envelope:                       | -   |
| High luminance light source:                        | No   |                                 |     |
| Anti-glare shield:                                  | No   | Dimmable:                       | No  |

## Product parameters

| Parameter                                                                                                                                      | Value                    | Parameter                                                                                                                                                  | Value                  |
|------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| <b>General product parameters:</b>                                                                                                             |                          |                                                                                                                                                            |                        |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer                                                                  | 6                        | Energy efficiency class                                                                                                                                    | G                      |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 400 in Narrow cone (90°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000                  |
| On-mode power ( $P_{on}$ ), expressed in W                                                                                                     | 6,0                      | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal                                                                               | 0,00                   |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal                                                | -                        | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | 80                     |
| Outer dimensions without                                                                                                                       | Height                   | Spectral power distribution in the                                                                                                                         | See image in last page |
|                                                                                                                                                | Width                    |                                                                                                                                                            |                        |
|                                                                                                                                                | Depth                    |                                                                                                                                                            |                        |

|                                                                                                                         |      |                                                                    |                                      |  |
|-------------------------------------------------------------------------------------------------------------------------|------|--------------------------------------------------------------------|--------------------------------------|--|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)                       |      |                                                                    | range 250 nm to 800 nm, at full-load |  |
| Claim of equivalent power <sup>(a)</sup>                                                                                | Yes  | If yes, equivalent power (W)                                       | 47                                   |  |
|                                                                                                                         |      | Chromaticity coordinates (x and y)                                 | 0,379<br>0,385                       |  |
| <b>Parameters for directional light sources:</b>                                                                        |      |                                                                    |                                      |  |
| Peak luminous intensity (cd)                                                                                            | -    | Beam angle in degrees, or the range of beam angles that can be set | 65                                   |  |
| <b>Parameters for LED and OLED light sources:</b>                                                                       |      |                                                                    |                                      |  |
| R9 colour rendering index value                                                                                         | 55   | Survival factor                                                    | -                                    |  |
| the lumen maintenance factor                                                                                            | -    |                                                                    |                                      |  |
| <b>Parameters for LED and OLED mains light sources:</b>                                                                 |      |                                                                    |                                      |  |
| displacement factor (cos $\phi_1$ )                                                                                     | 0,64 | Colour consistency in McAdam ellipses                              | 4                                    |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b) | If yes then replacement claim (W)                                  | -                                    |  |
| Flicker metric (Pst LM)                                                                                                 | 0,0  | Stroboscopic effect metric (SVM)                                   | 0,0                                  |  |

(a) - : not applicable;

(b) - : not applicable;