

Java

Deling	5/32 cut pile	ISO 2424
Poolsamenstelling	100% PES	ISO 2424
Tuftdoek	Woven	ISO 2424
Rug	AB, Vilt	ISO 2424
Breedte	400 cm, 500 cm	± 1% EN 984
Poolgewicht	1100 gr/m ²	ISO 8543
Totaalgewicht	AB : 2000 gr/m ² Vilt : 2100 gr/m ²	± 15% ISO 8543
Poolhoogte	12 mm	± 2 mm ISO 1766
Totale hoogte	AB : 14 mm Vilt : 15 mm	ISO 1765
Aantal noppen	73080 /m ²	-7.5% .+10% ISO 1763
Brandclassificatie	Cfl-S1	EN 13501-1
Gebruikzone	Medium domestic use (22)	EN 1307
Gut nr.	2911D8AB	www.pro-dis.info
Warmtedoorlaatbaarheid	ca. 0.06 (0.6 TOG) M ² KW	ISO 8302
Lichtechtheid	≥ 5	105-B02
Wrijftechtheid	≥ 4	105-X12
Waterechtheid	≥ 4	105-E01

Floorsymbols



Certificaten



2021
Condor Carpets
Euroweg 3
8061 SB Hasselt
EN1307
DOP: C-025AJ055
Reaction to fire:
Cfl-s1
1658
Slip resistance: DS
AB
Resilient floor
covering to be
used within a
building



2021
Condor Carpets
Euroweg 3
8061 SB Hasselt
EN1307
DOP: C-025FJ055
Reaction to fire:
Cfl-s1
1658
Slip resistance: DS
Vilt
Resilient floor
covering to be
used within a
building





