




OHIO

Kleuren	Coloris	Farben	Colours
4 colours			
8112 Berber			
8114 Rust			
8122 Silver			
8124 Grey			

<u>Fabricagemethode</u>	<u>Méthode de fabrication</u>	<u>Herstellungsverfahren</u>	<u>Manufacturing process</u>
Getuft 1/4" lussen pool	Tuftée 1/4" bouclé	Getufted 1/4" Schlinge	Tufting 1/4" loop-pile
<u>Poolsamenstelling</u>	<u>Composition du velours</u>	<u>Polmateriaal</u>	<u>Pile content</u>
100% polypropylene	100% polypropylene	100% polypropylene	100% polypropylene
<u>Tuftdoek</u>	<u>Support</u>	<u>Trägermateriaal</u>	<u>Primary backing</u>
Geweven PP	Tissé PP	PP Gewebe	Woven PP
<u>Rug</u>	<u>Dossier</u>	<u>Rückenausrüstung</u>	<u>Secondary backing</u>
Vlies	Feutre	Vlies	Felt
<u>Poolgewicht</u>	<u>Poids du velours</u>	<u>Polgewicht</u>	<u>Pile weight</u>
ca. 580 gr/m2.	ca. 580 gr/m2.	ca. 580 gr/m2.	ca. 580 gr/m2.
<u>Oppervlak poolgewicht</u>	<u>Poids de surface</u>	<u>Polschicht gewicht</u>	<u>Surface pile weight</u>
ca. 410 gr/m2	ca. 410 gr/m2	ca. 410 gr/m2	ca. 410 gr/m2
<u>Totaalgewicht</u>	<u>Poids total</u>	<u>Gesamtgewicht</u>	<u>Total weight</u>
Vlies : ca. 1735 gr/m2.	Feutre : ca. 1735 gr/m2.	Vlies : ca. 1735 gr/m2.	Felt : ca. 1735 gr/m2.
<u>Poolhoogte</u>	<u>Hauteur du poil</u>	<u>Polhöhe</u>	<u>Pile height</u>
ca. 5,5 mm.	ca. 5,5 mm.	ca. 5,5 mm.	ca. 5,5 mm.
<u>Totale hoogte</u>	<u>Hauteur total</u>	<u>Gesamthöhe</u>	<u>Total height</u>
Vlies : ca. 8,5 mm.	Feutre: ca. 8,5 mm.	Vlies : ca. 8,5 mm.	Felt : ca. 8,5 mm.
<u>Aantal noppen</u>	<u>Nombre de points</u>	<u>Noppenzahl</u>	<u>Number of knots</u>
ca. 44.170 m2	ca. 44.170 m2	ca. 44.170 m2	ca. 44.170 m2
<u>Breedte</u>	<u>Largeur</u>	<u>Breite</u>	<u>Width</u>
400 + 500 cm.	400 + 500 cm.	400 + 500 cm.	400 + 500 cm.
<u>Lichtechtheid</u>	<u>Résistance à la lumière</u>	<u>Lichtechtheit</u>	<u>Light fastness</u>
ISO 105 B02: 5 tot 8	ISO 105 B02: 5 à 8	ISO 105 B02: 5 bis 8	ISO 105 B02: 5 to 8
<u>Waterechtheid</u>	<u>Résistance à l'eau</u>	<u>Wasserechtheid</u>	<u>Water resistance</u>
EN 1307, annex F: 5	EN 1307, annex F: 5	EN 1307, annex F: 5	EN 1307, annex F: 5
<u>Brandklasse</u>	<u>Classement feu</u>	<u>Brandverhaltensklasse</u>	<u>Fire Class</u>
Vlies : Efl (EN13501-1)	Feutre: Efl (EN13501-1)	Vlies : Efl (EN13501-1)	Felt : Efl (EN13501-1)
<u>Warmteoorlaatweerstand</u>	<u>Résistance thermique</u>	<u>Wärmedurchlasswiderstand</u>	<u>Thermal resistance</u>
0,120 m2 K/W	0,120 m2 K/W	0,120 m2 K/W	0,120 m2 K/W
<u>Geluidsisolatie</u>	<u>Isolation aux bruits d'impact</u>	<u>Trittschalldämmung</u>	<u>Sound insulation</u>
10,0 dB	10,0 dB	10,0 dB	10,0 dB
<u>Bijzonderheden</u>	<u>Caractéristiques</u>	<u>Besonderheiten</u>	<u>Characteristics</u>

AB

Felt



Timzo tufting Industry BV
8280 AA Genemuiden - Holland - Postbus 7 (Post)
Tel. 0031 (0)383854477 Fax 0031 (0)383856571

8281 JD Genemuiden - Holland - Nijverheidstraat 27 (Office)
Email: carpets@timzo.nl Online: www.Timzo.nl