

Java

Teilung	5/32 cut pile	ISO 2424
Material	100% PES	ISO 2424
Träger	Woven	ISO 2424
Rueckenausrüstung	TR (Textilrucken), Filz	ISO 2424
Bahnbreite	400 cm, 500 cm	± 1% EN 984
Oberflächen- / Florgewicht	1100 gr/m ²	ISO 8543
Gesamtgewicht	TR (Textilrucken) : 2000 gr/m ² Filz : 2100 gr/m ²	± 15% ISO 8543
Polhöhe	12 mm	± 2 mm ISO 1766
Totale Höhe / Gesamtdicke	TR (Textilrucken) : 14 mm Filz : 15 mm	ISO 1765
Noppenzahl	73080/m ²	-7.5% .+10% ISO 1763
Brandverhalten	Cfl-S1	EN 13501-1
Verwendungsbereich	Medium domestic use (22)	EN 1307
GUT Nr.	2911D8AB GUT	www.pro-dis.info
Lichtechtheit	≥ 5	105-B02
Reibechtheit	≥ 4	105-X12
Wasserechtheit	≥ 4	105-E01

Teppichsymbole



Zertifikats

 2021 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-025AJ055 Reaction to fire: Cfl-s1 1658 Slip resistance: DS TR (Textilrucken) Resilient floor covering to be used within a building	 2021 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-025FJ055 Reaction to fire: Cfl-s1 1658 Slip resistance: DS Filz Resilient floor covering to be used within a building
---	--

